

**WHEN MBS FIGURES ARE SPECIFIED ON THE EQUIPMENT  
THE SAFETY FACTOR YOU CHOOSE TO APPLY TO A RECOVERY SITUATION  
WILL DICTATE WHAT MBS WILL BE NEEDED BY THE EQUIPMENT**

**EXAMPLE 1:**

3000KG OBJECT BEING RECOVERED  
SAFETY FACTOR OF 2 APPLIED  
SOFT SHACKLE NEEDS TO BE RATED 6,000KG / 6T OR ABOVE  
SNATCH RING OR RECOVERY RING NEEDS TO BE RATED AT  
6,00KG / 6T / 5.88kN OR ABOVE

**EXAMPLE 2:**

2500KG OBJECT BEING RECOVERED  
SAFETY FACTOR OF 3 APPLIED  
SOFT SHACKLE NEEDS TO BE RATED 7,500KG / 7.5T OR ABOVE  
SNATCH RING OR RECOVERY RING NEEDS TO BE RATED AT  
7,500KG / 7.5T / 73.6kN OR ABOVE

**EXAMPLE 3:**

3000KG OBJECT BEING RECOVERED  
SAFETY FACTOR OF 5 APPLIED  
SOFT SHACKLE NEEDS TO BE RATED 15,000KG / 15T OR ABOVE  
SNATCH RING OR RECOVERY RING NEEDS TO BE RATED AT  
15,000KG / 15T / 147.1kN OR ABOVE

